

技术参数(Technical Parameter):

4 (Item					
R + S 5 6 Ball mill model	B 1200X4500	B 1500X5700	B 1830X7000		
- . S 5 6 Classifier model	HFZ050	HFZ100	HFZ200		
r s t 7 8 9: kW; General power of the whole	C 75	C 145	C 225		
< + p: Kg/h; Processing capacity: Kg/h;	800- 1000	1200- 1800	3500- 4000		
s p: kg/h; Production capacity: Kg/h;	480- 600	720- 1080	2100- 2400		
@R: um; Particle size	5D50	5- 50	4 000		
- . = R Classifying granularity	D97	D97	2100- 2400	Tf0. 72 - 26. 04 TD (C)	T TD1. D 0. 48 Tc (12) Tj0. 6 Tc (0) Tj0. 48
^ > ? @: m ² ; Fliter area	E 50	E 70	HFZ050		
XYAR: mg/m ³ ; Thickness of dust	C 40	C 40	C		
G S d Operation	128X54				

3%) # \$ % & ' # F G 325 ((5D) * (All of the parameters above are according to 325 mesh quartz) 3

2) +, V - . \$ a / y z N # \$ % & O 1 % 2 (As different material from different places, the parameter is just for your reference) 3

鉴定成果(Certification)

