



	mm	h mm	mT	mm	kw	kw	m/s	kg	mm				
									A	B	C	D	E
RCDA-5	500	150	60	90	1	0.15	4.5	450	340	430	500	710	340
RCDA-6	600	175	60	120	1.6	0.37		620	500	450	600	910	500
RCDA-6.5	650	200	70	150	2	0.37		750	780	510	710	990	650
RCDA-8	800	250	70	180	4	0.37		980	870	550	810	1080	740
RCDA-10	1000	300	70	230	6	0.45		1330	1250	590	1100	1400	1040
RCDA-12	1200	350	70	280	8	0.45		1950	1400	640	1300	1600	1240
RCDA-14	1400	400	70	330	12	0.8		2870	1560	530	1460	1910	1400
RCDA-16	1600	450	70	380	15	0.8		3800	1760	530	1660	2010	1600
RCDA-18	1800	500	70	430	20	1.3		4500	2000	850	1880	2360	1800

T1 T2 T3

90mT 120mT 150mT

RCDA- T

	mm	h mm	mT	KW	KW	mm			m/s	kg	
						A	B	C			
RCDA-6.5	650	200	90	3.0	0.37	1190	1090	570	5.8	750	
			T2	120	5.0	0.37	1190	1090		600	1000
			T3	150	8.0	0.37	1190	1090		625	1270
RCDA-8	800	250	90	5.0	0.37	1280	1180	650		1270	
			T2	120	9.0	0.55	1280	1180		700	1700
			T3	150	13.0	0.55	1280	1180		750	2170
RCDA-10	1000	300	90	7.5	0.55	1480	1380	730		2030	
			T2	120	12.5	0.55	1480	1380		780	2690
			T3	150	16.5	1.1	1480	1380		850	3450
RCDA-12	1200	350	90	10.0	1.1	1750	1600	860	3000		
			T2	120	14.0	1.1	1750	1600	910	4050	
			T3	150	21.0	1.1	1750	1600	920	5140	
RCDA-14	1400	400	90	14.0	1.1	1980	1780	920	4350		
			T2	120	18.0	0.75x 2	1980	1780	1000	6390	
			T3	150	26.0	0.75x 2	1980	1780	1100	7340	
RCDA-16	1600	450	90	15.0	1.5	2200	1980	1100	6070		
			T2	120	22.0	2.2x 2	2200	1980	1130	8020	
			T3	150	32.0	2.2x 2	2200	1980	1170	10120	
RCDA-18	1800	500	90	19.0	2.2x 2	2300	2150	1120	8200		
			T2	120	28.0	2.2x 2	2300	2150	1200	10780	
			T3	150	38.0	2.2x 2	2300	2150	1250	13350	
RCDA-20	2000	550	90	24.0	2.2x 2	2660	2500	1250	10800		
			T2	120	32.5	2.2x 2	2660	2500	1350	13900	
			T3	150	45.0	2.2x 2	2660	2500	1380	17230	

